


2 WAY NC DIRECT ACTING SOLENOID VALVE, 1/8 AND 1/4



normally closed

TYPE: D262/63

TECHNICAL SPECIFICATIONS

- Media: water, oil, air
- Media temperature: 14° F - 266° F
- Ambient temperature: 14° F - 122°F
- Body material: brass (C37700)
- Orifice material: stainless steel
- Operator material: stainless steel
- Seal material: VITON®
- Coil power: AC = 15 VA (holding)
AC = 30 VA (inrush)
DC = 10 W
- Protection class: NEMA 4 (with connector)



OPTIONS

- Normally open (Ex code RDD263DVGN)
- Manual override (Ex code D262DVHNM)
- EPDM seal for air and hot water MAX 248°F (Ex code D262DEHN)
- RUBY seal 14° F - 356°F for high temperature with class "H"
- Coils (Ex code D262DRCN 7201)
- CE coils on request (Ex code 7200)

SELECTION TABLE	VALVES	pipe size	orifice	CV flow rate	Operating Pressure Differential			COILS	
					min	liquids	gas		
	Code	(NPT)	(inch)	(gpm)	(psi)	ac	dc	Code	(Volts/Hz)
	D262DVAN	1/8	3/64	0.03	0	435	435	725R	24/dc
D262DVCN	1/8	1/16	0.09	0	348	348	720R	24/50 - 60	
D262DVG <u>N</u>	1/8	3/32	0.24	0	261	232	740R	110/50 - 120/60	
D262DVH <u>N</u>	1/8	1/8	0.31	0	217	116	760R	200/50 - 220/60	
D263DVCN	1/4	1/16	0.09	0	348	348	770R	230/50 - 240/60	
D263DVG <u>N</u>	1/4	3/32	0.24	0	261	232			
D263DVH <u>N</u>	1/4	1/8	0.31	0	217	116			
D263DVL <u>N</u>	1/4	5/32	0.42	0	116	72.5			
D263DV <u>N</u> N	1/4	3/16	0.52	0	72.5	36			
D263DV <u>P</u> N	1/4	1/4	0.6	0	43.5	14.5			

DIMENSIONS & WEIGHTS	pipe size		A	B	C	D	weight
	(NPT)	(inch)	(inch)	(inch)	(inch)	(inch)	(lbs.)
	1/8	1.57	3.05	1.25	0.43	0.57	
1/4	1.57	3.05	1.25	0.43	.57		

