


## 2 WAY NC PILOT OPERATED SOLENOID VALVE FOR STEAM 3/4" To 1"



**normally closed**

**TYPE: D606/622**

### TECHNICAL SPECIFICATIONS

- Media: hot water, steam
- Media temperature: 140° F - 356° F
- Ambient temperature: 14° F - 158° F
- Body material: brass (CW617N EN 12165)
- Orifice material: stainless steel (AISI 303 EN 10088-3)
- Operator material: stainless steel
- Diaphragm material: PTFE
- Coil power: AC = 18 VA (holding)  
AC = 36 VA (inrush)  
DC = 22 W
- Protection class: NEMA 4 (with connector)



### NOTE

For correct functioning, the minimum media temperature of the solenoid valve cannot be below 140° F.

SELECTION TABLE	VALVES	pipe size	orifice	CV flow rate	Operating Pressure Differential			COILS class "H" only	
					min	max			
	Code	(NPT)	(inch)	(gpm)	(psi)	liquids ac	gas dc	Code	(Volts/Hz)
	D606DTY	3/4	1"	8.39	14	150	150	71Z1	12/vdc
	D622DTY	1	1"	8.39	14	150	150	72Z1	24/vdc
								7201	24/50 - 60
								7401	110/50 - 120/60
								7601	200/50 - 220/60
								7701	230/50 - 240/60

DIMENSIONS & WEIGHTS		pipe size	A	B	C	weight
		(NPT)	(inch)	(inch)	(inch)	(lbs.)
		3/4	3.78	4.88	.90	1.3
1	3.78	4.88	.90	1.3		