

UL COILS FOR CV CORP INTERNATIONAL SOLENOID VALVES

The coils that CV Corp. produces are designed for continuous duty in conformity to the UL429 and CSA C 22.2 No. 139 safety standards. They are encapsulated in a self-extinguishing synthetic material and offer high mechanical protection and excellent thermal dissipation. They are fully interchangeable on all CV Corp. solenoid valves, thereby reducing warehouse inventories.

SERIES: 200R/700R

TECHNICAL SPECIFICATIONS

Electrical connection: faston connection 6.3x0.8 (DIN 43340)

Series 200R: connection to DIN 46244

Series 700R: connection to DIN 43650A

Protection class: NEMA 4 (with connector)

Voltage tolerance: +10% to -15% ac / $\pm 5\%$ dc

Operation: continuous

Coil power:	Series 200R	Series 700R
	AC = 9 VA	15 VA (holding)
	AC = 14 VA	30 VA (in rush)
	DC = 6 W	10 W



VOLTAGE & FREQUENCY	Coils series 200R	Coils series 700R	(Volts/Hz)
	215R	715R	12/dc
	225R	725R	24/dc
	220R	720R	24/50 - 60
	240R	740R	110/50 - 120/60
	260R	760R	200/50 - 220/60
	270R	770R	230/50 - 240/60

